Machine configuration:A4301757

	Кеу	Name	
Homologationtype	3232	3232	
machine no.	A4301757	A4301757	
machine no.	A4301757	A4301757	
		Serial number	
Gearbox	GBA25	F343316	
Cabine	K08	X-2015000969	
Motor	F4DFE4138*B001	001387527	
Rearaxle	GPA54	F342583	
Frontaxle	406007	40600701000927	
Transmission	GTA2554	10078001	
Type/Subtype			
A43	ARION 460-430		
	ARION 460-430		
TH_102_4320	440/65 R28 standard tyres / fixed rim 440/65 R28 Firestone Performer 65 / fixed rim		
TH_102_4326			
TH_103_56B0	480/70 R38 standard tyres / fixed rim		
TH_103_56B6	480/70 R38 Firestone Performer 70 / fixed rim		
TH_105_0733	0733_21460460/2554 0001 fix fravel & fravel black		
TH_515_0001	0001_fix.fr.axl & fr.wei.block		
TH_517_0004	0004_High roof & 4 rear lights		
TH_538_0010	0010_Cab green bonnet		
TH_B02_0010	Front weight carrier 115 kg		
TH_B04_0000	Without linkage-mounted weight block		
TH_B06_0000	Without front PTO		
TH_B10_0040	Front loader brackets for ELECTROPILOT		
TH_B14_0000	Not relevant		
TH_B16_0010	Bonnet protector bar		
TH_102_0030	CIS, black/white control terminal		
TH_104_0025	Multifunction control lever for ELECTROPILOT		
TH_I10_0000	Without ISOBUS equipment		
TH_I12_0010	Additional operating panel for hydraulic functions		
TH_I22_0000	Not prepared for AUTO PILOT/GPS PILOT		
TH_I24_0000	Without SAT 900 GNSS receiver		
TH_I26_0000	Without TELEMATICS		
TH_I28_0000	Without terminal		
TH_J02_0060	Rear linkage, electrohydraulic, 5.75 t		
TH_J04_0300	Lower links, cat. 3 with hook		
TH_J06_0200	2 lower link stabilisers, mechanical		
TH_J08_0130	Top link, cat. 3/2 with hook		
TH_J10_1010	Pick-up hitch, hydraulic push out		
TH_J14_0000	Without drawbar		
TH_J16_0000	Without rear clevis		
TH_J18_0000	Without linkage drawbar and ball set		
TH_J40_0030	Hydraulic brakes.		
TH_K02_0091	Open centre hydraulics, 100 l/min		
TH_K04_0150	5 spool valves, 3 x mechanical, 2 x electrohydraulic (CIS, FL)		
TH_K10_0000	Without front hydraulic outlets		
TU K12 0000	Without Power Boyou	ad	

TH_K12_0000 Without Power Beyond

TH_N02_0010 QUADRISHIFT transmission

TH_N04_0200 Transmission ratio 40 km/h

TH_N06_0110Front axle, standardTH_N08_0120Rear axle, standard

TH N10 0020

PTO: 540/540 FCO + 1000 rpm

Type/Subtype	
TH_N26_0000	Without wheel spacers for rear axle
TH_N30_0010	PTO control, rear
TH_N32_0000	Without automatic PTO engagement/disengagement, rear
TH_N34_0000	Without rear wheel weights
TH_P02_0040	115 hp rated output, 120 hp max. output, ECE R 120
TH_P04_0010	Without diesel pre-filter
TH_P06_0030	Battery master switch, electronic
TH_P08_0020	White diesel
TH_P10_0010	Cold start kit down to -30 °C
TH_Q02_0030	6-pillar PANORAMIC cab
TH_Q04_0210	PANORAMIC roof
TH_Q08_0020	Rear window wiper
TH_Q14_0015	Mirrors: 2 external, 1 internal and 1 hitch
TH_Q18_0010	Lateral mudguard extensions
TH_Q20_0010	Screen mounting rail
TH_Q30_0010	Additional interface sockets
TH_Q40_0030	2x high-level headlights on the roof, halogen
TH_Q44_0131	Work lights: 2 x bonnet, 2 x front, adjustable and 4 x rear
TH_R00_0000	Colour, CLAAS Green
TH_R04_0130	Driver's seat, fabric, air suspension
TH_R06_0020	Passenger seat with safety belt
TH_R08_0010	Air conditioning
TH_R10_0010	Preparation for radio
TH_R12_0020	Cooler compartment for 1.5 I bottle (under the instructor's seat)
TH_R20_0000	Without dynamic steering
TH_S01_0020	1 wheel chock
TH_S01_0140	Sticker 40 km/h
TH_S02_0001	Sticker, standard
TH_S04_0010	Right-hand drive
TH_S06_0021	Rotating beacon, left
TH_S08_0001	Equipment - European Union
TH_T02_0010	Truck transport
A43/100	ARION 440